

# Certificate of Compliance



You have been awarded:

## **Intertek WH US Mark for Category D - Door/frame Assemblies**

Standards: UL 10(c) (2016), UL 10(b) (2008) (R2020), NFPA 252 (2022)


Certificate number: WHI24-18405339

This is a certificate of compliance to certify that the bearer has successfully completed the requirements of the above scheme which include the testing of products, the initial assessment, and are subject to continuing annual assessments of their compliance and testing of samples of products taken from production (as applicable to the scheme) and has been registered within the scheme for the products detailed.

**Organization:** Abanos Furniture & Decoration Industry LLC  
P.O. Box 114480  
Dubai Investment Park 1  
Dubai  
United Arab Emirates

**Product:** Abanos – FD90 SD – 64mm thick Palm Strand Board Fire Door and Frame Assembly - 90-Minute – UL 10C  
*Spec ID:* 78324  
*Fire Rating:* 90 Min PP Category D Door/Frame Assemblies  
*Listing Information:* See following page(s)

**Certification body:** Intertek Testing Services NA, Inc.  
**Initial registration:** July 11, 2024  
**Date of expiry:** December 31, 2024  
**Issue status:** 1

Authorized By:   
**Jean-Philippe Kayl, Director of Certification**

Intertek Testing Services NA, Inc.  
545 E. Algonquin Road, Ste H., Arlington Heights, IL 60005 USA  
Phone: 847-439-5667 Fax: 847-439-7320

[www.intertek.com](http://www.intertek.com)

The certificate and schedule are held in force by regular annual surveillance visits by Intertek Testing Services NA, Inc. and the reader or user should contact Intertek to validate its status. This certificate remains the property of Intertek Testing Services NA, Inc. and must be returned to them on demand. This Certificate is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this certificate. Only the Client is authorized to permit copying or distribution of this certificate and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.

## LISTING INFORMATION

### Product Covered

Abanos – FD90 SD – 64mm thick Palm Strand Board Fire Door and Frame Assembly - 90-Minute – UL 10C

### Product Description

Abanos – FD90 SD – 64mm thick Palm Strand Board Fire Door and Frame Assembly.

Door frame is constructed with Palm Strand Board with MDF cladding. Overall size - 63mm wide x 120mm depth, stop height - 18mm.

Door leaf is constructed using Palm Strand Board and Calcium Silicate Board layers with overall leaf thickness: 64mm.

### Tested Sizes:

Door frame - 1096 x 2353 x 120mm (w x h x jamb depth)

Door leaf - 1000 x 2300 x 64mm (w x h x thickness)

### Limitations:

Minimum latch throw: 19mm

Supporting construction - Masonry wall assemblies.

### FIRE RATINGS

The product noted above has been evaluated according to the requirements of the standard UL 10C and has qualified for up to **90 minutes (1 ½ hour)** positive pressure fire rating.

Also meets the requirements of UL 10B (Neutral Pressure Fire Rating) and NFPA 252 (Positive Pressure Fire Rating).

Note - Entire Assembly (door, frame and hardware) is shipped from the manufacturing facility as a complete package.